

Emergency Discharge Control Procedure For Cargo Tank Motor Vehicle

Per 49 CFR §177.840L

A COPY OF THIS PROCEDURE MUST BE CARRIED IN THE POWER UNIT OF THE CARGO TANK MOTOR VEHICLE AT ALL TIMES

Company or District: _____

Date: _____

Equipment Type: TRANSPORT TRAILER

Self-Closing Internal
Stop Valve Actuation:

AIR

BOBTAIL

CABLE

PTO (Rego Flowmatic)

Passive Shutdown System

Thermal Fusible Link

Off-Truck Radio Frequency Device

Mechanical Shutdown Control
Stations/Engine Kill Switch

From Cargo Tank Manufacturer's Data Plate

Vehicle Number: _____

Cargo Tank S/N: _____

Max. Work. Press _____ PSIG

EMERGENCY SHUT-DOWN CONTROL(S) ARE LOCATED:

EMERGENCY SHUT-DOWN PROCEDURE: 1) ALWAYS KEEP UPWIND OF A FUEL LEAK

2) NEVER ENTER A GAS VAPOR CLOUD

Approach vehicle and emergency controls only if it is safe to do so

3) _____

4) _____

5) _____

After actuating any of the emergency shut down devices, move away from the vehicle and be sure that you keep all other unauthorized persons away from the vehicle until all flow of gas from the vehicle has stopped. If fire is present, keep everyone away from the vehicle until emergency response officials have arrived, the flow of gas has stopped, flames are extinguished, metal parts are cooled and the area is secure.

Do not enter or allow anyone other than Company officials to enter the vehicle cab.